Worldwide Leader In Advanced Cleaning Systems



SUPER MAXTM 12800 AF with Daimer®'s Phosphatizing System







www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com Daimer®'s industry-leading Super Max[™] pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Max[™] pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technology[™] for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.





- Features Daimer®'s phosphatizing system for the pretreatment of metal surfaces to prevent rust and corrosion, and to prepare surfaces for the application of paint primer and powder coating.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.
- Free Skid Configuration for Trailer Mounting

| Model | Super Max 12800 AF |
|-------------------------------|---|
| Pressure | 1000 PSI |
| Flow Rate | 2 GPM |
| Temp. Options | Cold, hot water |
| Steam Temp. / Hot Water Temp. | N/A / Up to180°F |
| Standard Power Method | Electric: 110V-120V, single phase, 60 Hz |
| Motor Size | Heavy duty 1.5 HP - NEMA |
| Minimum Generator Size | 5000 watts |
| Gasoline/Diesel Fuel Capacity | N/A |
| Ignition System | Electronic direct spark |
| Heating Method | Heating oil; diesel; kerosene |
| Heating Fuel Capacity | 9 gallons |
| Heater Exchange Coil | Heavy duty schedule 80 heating coil |
| Heater Response Time | Converts cold to hot water - approx. 30 seconds |
| Operating Time | Continuous use |
| Pump Drive Method | Direct drive |
| Chemical Infusion | Yes – high pressure injection |
| Wand Included | Dual lance wand |
| Nozzles Included | 0°, 15°, 25°, 40°, steam nozzles |
| Pressure Hose | 50' high pressure steam hose |
| Dimensions | 25" w. x 32" d. x 42" h. |
| Weight | 450 lbs. |
| AST® Technology | See the Super Max™ 12800 AST |
| Phosphatizing System | Yes |
| Wet Sandblasting System | See the Super Max™ 12800 WS |
| Multi-Gun Operation | Optional – call for pricing |
| Trailer Mount | Wheels removed |
| | |



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com