Worldwide Leader In Advanced Cleaning Systems



SUPER MAX<sup>TM</sup> 15800 AF with Daimer®'s Phosphatizing System







www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com Daimer®'s industry-leading Super Max<sup>™</sup> pressure washers are available in more than 400 models and configurations. The product line includes general purpose mobile machines, multi-gun stationary systems, pressure washers designed for indoor use and equipment manufactured for auto car detailing. The machines are available with pressure levels as high as 8000 psi and temperatures to 330°F. Daimer® also offers systems that support wet steam cleaning for cutting grease. Daimer®-only technologies available in Super Max<sup>™</sup> pressure washers include: Long Hose Technology that supports hoses up to 300 feet in length and Auto Shutoff Technology<sup>™</sup> for reduced system wear. Daimer® pressure washers are available in 50 Hz and 60 Hz configurations.





- Features Daimer®'s phosphatizing system for the pretreatment of metal surfaces to prevent rust and corrosion, and to prepare surfaces for the application of paint primer and powder coating.
- Available in a variety of power configurations for worldwide requirements, including: 110-120V, 208V, 220-240V, 380V, 415V, 440-480V, and 575V; single and three phase; 50 or 60 Hz. Please contact us for pricing.

Model	Super Max 15800 AF
Pressure	2000 PSI
Flow Rate	4 GPM
1 10 11 1 1000	
Temp. Options	Cold, hot water
Steam Temp. / Hot Water Temp.	N/A / Up to 180°F
Standard Power Method	Electric: 220V-240V, single phase, 60 Hz
Motor Size	Heavy duty 5.0 HP - NEMA
Minimum Generator Size	N/A
Gasoline/Diesel Fuel Capacity	N/A
Ignition System	Electronic direct spark
Heating Method	Heating oil; diesel; kerosene; natural gas; propane
Heating Fuel Capacity	9 gallons
Heater Exchange Coil	Heavy duty schedule 80 heating coil
Heater Response Time	Converts cold to hot water - approx. 30 seconds
Operating Time	Continuous use
Pump Drive Method	Direct drive
Chemical Infusion	Yes – high pressure injection
Wand Included	Dual lance wand
Nozzles Included	0°, 15°, 25°, 40°, steam nozzles
Pressure Hose	50' high pressure steam hose
Dimensions	52" w. x 23" d. x 50" h.
Weight	1025 lbs.
AST® Technology	See the Super Max ™ 15800 AST
Phosphatizing System	Yes
Wet Sandblasting System	See the Super Max™ 15800 WS
Multi-Gun Operation	Optional – call for pricing
Trailer Mount	N/A



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com