Worldwide Leader In Advanced Cleaning Systems



VAPOR-FLO® 7940





www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com The Vapor-Flo® line of pressure offers all-electric performance designed for reduced noise and no fumes. The machines are heated and powered with electricity and are available in more than 80 configurations designed to meet the needs of domestic and overseas customers. The models include stationary models for fixed applications and several mobile models in different case designs. Daimer® case designs include a chemical resistant stainless steel housing and top loading model that allows for manual refills and operation away from a fixed water source. All Vapor-Flo® machines are covered by company backed warrantees for water pumps, motors and other parts.



- Electric powered and electric heated for maximum efficiency and user convenience.
- All electric pressure washers generate no exhaust.
 Their clean-burning operation is ideal for indoor commercial and industrial applications.
- This **220V-240V**, **single phase**, **50 Hz machine** is also available in 220V-240V, single phase, 60 Hz. See the Vapor-Flo® 8940.
- Top temperatures reach up to 79.4°C for optimum cleaning power.

| Model | Vanor Flo 7940 |
|-------------------------------|--|
| | Vapor-Flo 7940 |
| Pressure | 2175 PSI (150 bar) |
| Flow Rate | 7.6 LPM |
| Temp. Options | Cold, hot water |
| Hot Water Temp. | Up to 79.4°C |
| Standard Power Method | Electric: 440V, three phase 50 Hz |
| Optional Power Method | Electric: 440V, three phase 60 Hz / 480V, three phase 60 Hz |
| Motor Size | Heavy duty 4.0 HP |
| Minimum Generator Size | Contact Daimer |
| Gasoline/Diesel Fuel Capacity | N/A |
| Ignition System | N/A |
| Heating Method | Electric – 30 kW |
| Heating Fuel Capacity | N/A |
| Heater Exchange Coil | High-pressure stainless steel |
| Heater Response Time | Converts cold to hot water - approx. 20 seconds |
| Operating Time | Continuous use |
| Pump Drive Method | Direct drive |
| Chemical Infusion | Yes - siphon type standard/foam lance injection |
| Wand Included | Durable 76.2 cm trigger wand with quick disconnect |
| Nozzles Included | 25° stainless steel pressure nozzle with incorporated filter |
| Pressure Hose | 9.8m high pressure, double layered hose |
| Dimensions | 63.5 cm w. X 88.9 cm d. X 81.3 cm h. |
| Weight | 86.2 kg |
| Wall Mount | Yes |
| Trailer Mount | N/A |



www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com