

## **XTREME POWER® HSC 17200**





www.daimer.com 16 Tower Office Park Woburn, MA 01801 (800) 471-7157 sales@daimer.com Daimer®'s XTreme Power® HSC line includes more than 20 models designed for industrial, commercial and residential applications. The machines is composed of a variety of machines designed for optimum performance on a variety of surfaces. The HSC line includes: self-contained floor cleaners, high-performance units for cleaning up after water damage as well as machines with powered spinning heads. The powered spinning heads come in two sizes, 9-inch and 19-inch, for large and small applications. Several machines are optimized to handle deep-cleaning on porous tile floors. All the machines are covered by Daimer®'s exclusive warrantee options for years of worry free operation.



The XTreme Power  $\ensuremath{\mathbb{R}}$  HSC 17200 can be used as several machines in one:

- Multi-Surface, Portable 2000 PSI Hard Surface Spinner Cleaning Machine - Configured as is.
- Commercial Steam Pressure Washer 2000 PSI, up to 4 GPM. Pressure washer wand included.
- Commercial Wall Cleaning System With optional 9" spinner head placed in hands or optional squeegee wand.
- Commercial Sludge Extractor Powerful 30 GPM for water damage restoration.

Model	XTreme Power HSC 17200
Pressure	2000 psi
Flow Rate	4 GPM
Temperature Options	Cold water, hot water, wet steam
	(steam cannot be used with spinner head)
Temperature (Hot/Steam)	Up to 180°F - 210°F / up to 330°F (not for use with spinner head)
Heating Method	Propane
Propane Tanks	50 lb. empty tank included
Heater Exchange Coil	Heavy duty schedule 80 heating coil
Spinner Diameter/Length/RPM	19 inches / 46 inches / 1000 RPM
Standard Power Method:	Electric: 220V-240V, single phase, 60 Hz
Pressure Washer	
Motor Size: Pressure Washer	Heavy duty 5.0 HP - NEMA
Ignition System	Electronic direct spark
Operating Time	Continuous Use
Continuous Water Feed	Yes. Connect hose directly to pressure washer.
Recovery Tank Size	10 gallons
Automatic Dump	Yes – Auto dump can be turned off if not required
Dumping Capacity	30 gallons/minute
Air Flow	212 cfm
Water Lift	147 inches
Motor: Extractor	Two - 3 stage vacuum motors
Power: Extractor	Electric: 120V
Heater Response Time	Cold water to hot water in approx. 30 seconds
Chemical Infusion	Yes – High pressure injection
Hoses: Vacuum/Dump/Steam	50' vacuum, 50' dump, 50' steam hoses included
Pressure Nozzles	0° (blast), 15°, 25°, 40°, steam nozzles
Wands Included	Durable 3' pressure wand with quick disconnect, 14.5" extraction squeegee wand
Optional Wands	12" 4-jet squeegee wand, 18" squeegee wand with 6 internal jets, 9" motorized spinner
Housing: Pressure Washer/Extractor	Pressure Washer: Steel - powder-coated, high-gloss,
	chip/chemical resistant
	Extractor: Heavy duty fiber composite
Color: Pressure Washer/Extractor	Red and White / Blue or Red
Dimensions: Pressure Washer/Extractor	48" w. x 41" d. x 50" h. / 16" w. 32" h. 21" l.
Weight: Pressure Washer/Extractor	900 lbs. / 90 lbs.

